



Slope Stability Analysis using Bishops Method Formulas

Calculators!

Examples!

Conversions!

Bookmark calculatoratoz.com, unitsconverters.com

Widest Coverage of Calculators and Growing - 30,000+ Calculators!

Calculate With a Different Unit for Each Variable - In built Unit Conversion!

Widest Collection of Measurements and Units - 250+ Measurements!

Feel free to SHARE this document with your friends!

Please leave your feedback here...





Open Calculator

Open Calculator

Open Calculator

Open Calculator

List of 35 Slope Stability Analysis using Bishops Method Formulas

Slope Stability Analysis using Bishops Method 🗗

1) Change in Normal Stress given Overall Pore Pressure Coefficient

$$\Delta \sigma_1 = rac{\Delta u}{R}$$

 $ex 6Pa = \frac{3Pa}{0.50}$

2) Change in Pore Pressure given Overall Pore Pressure Coefficient


fx $ig|\Delta \mathbf{u} = \Delta \mathbf{\sigma}_1 \cdot \mathbf{B}ig|$

3) Effective Angle of Internal Friction given Shear Force in Bishop's Analysis

$$\phi' = a anigg(rac{(ext{S} \cdot ext{f}_{ ext{s}}) - (ext{c}' \cdot ext{l})}{ ext{P} - (ext{u} \cdot ext{l})}igg)$$

 $\boxed{ 9.874119^\circ = a \tan \bigg(\frac{(11.07 \mathrm{N} \cdot 2.8) - (4 \mathrm{Pa} \cdot 9.42 \mathrm{m})}{150 \mathrm{N} - (20 \mathrm{Pa} \cdot 9.42 \mathrm{m})} \bigg) }$

4) Effective Angle of Internal Friction given Shear Strength



 $oxed{ex} 1.301768^{\circ} = a anigg(rac{0.025 ext{MPa} - 4 ext{Pa}}{1.1 ext{MPa} - 20 ext{Pa}}igg)$



5) Effective Cohesion of Soil given Normal Stress on Slice

 $\mathbf{c}' = \mathbf{r} - \left(\left(\sigma_{\mathrm{normal}} - \mathbf{u}
ight) \cdot an \left(rac{\phi' \cdot \pi}{180}
ight)
ight)$

Open Calculator

6) Effective Cohesion of Soil given Shear Force in Bishop's Analysis

 $\mathbf{c'} = \frac{(S \cdot f_s) - \left((P - (u \cdot l)) \cdot tan\left(\frac{\phi' \cdot \pi}{180}\right)\right)}{l}$

Open Calculator

7) Effective Stress on Slice

 $\mathbf{f}\mathbf{x} \mid \mathbf{\sigma}^{'} = \left(rac{\mathrm{P}}{1}
ight) - \Sigma \mathrm{U}$

Open Calculator 🗗

8) Factor of Safety given by Bishop

fx $f_{
m s} = m - (n \cdot r_{
m u})$

Open Calculator 🗗

 $\texttt{ex} \ 2.71 = 2.98 - (0.30 \cdot 0.9)$

9) Factor of Safety given Shear Force in Bishop's Analysis

 $\mathbf{f}_{s} = rac{\left(c' \cdot l
ight) + \left(P - \left(u \cdot l
ight)
ight) \cdot an\left(rac{\phi' \cdot \pi}{180}
ight)}{S}$

Open Calculator

 $= \frac{(4 \text{Pa} \cdot 9.42 \text{m}) + (150 \text{N} - (20 \text{Pa} \cdot 9.42 \text{m})) \cdot \tan \left(\frac{9.99^{\circ} \cdot \pi}{180}\right)}{11.07 \text{N}}$



© <u>calculatoratoz.com</u>. A <u>softusvista inc.</u> venture!



10) Height of Slice given Pore Pressure Ratio

 $\mathbf{z} = \left(rac{F_{\mathrm{u}}}{r_{\mathrm{u}} \cdot \gamma}
ight)$

Open Calculator

Open Calculator

Open Calculator 2

Open Calculator 🚰

Open Calculator

 $\mathbf{ex} \ 3.264815 \mathbf{m} = \left(\frac{52.89 \mathrm{kN/m^2}}{0.9 \cdot 18 \mathrm{kN/m^3}} \right)$


11) Horizontal Distance of Slice from Centre of Rotation

12) Length of Arc of Slice

13) Length of Arc of Slice given Effective Stress

= 12.5m = $\frac{150N}{10Pa + 2N}$

14) Length of Arc of Slice given Shear Force in Bishop's Analysis





© calculatoratoz.com. A softusvista inc. venture!




15) Normal Stress on Slice

$$\sigma_{normal} = \frac{P}{1}$$

Open Calculator

16) Normal Stress on Slice given Shear Strength



Open Calculator

$$23.28608 \mathrm{Pa} = \left(\frac{2.06 \mathrm{Pa} - 2.05 \mathrm{Pa}}{\tan \left(\frac{9.99^{\circ} \cdot \pi}{180} \right)} \right) + 20 \mathrm{Pa}$$

17) Overall Pore Pressure Coefficient

$$\mathbf{E} = rac{\Delta \mathbf{u}}{\Delta \sigma_1}$$

Open Calculator

$$\boxed{\textbf{ex}} 0.5 = \frac{3 \text{Pa}}{6 \text{Pa}}$$

18) Pore Pressure given Effective Stress on Slice

$$\Sigma U = \left(rac{P}{l}
ight) - \sigma^{'}$$

Open Calculator



19) Pore Pressure Ratio given Horizontal Width

fx $\left[\mathbf{r}_{\mathrm{u}}=rac{\mathbf{u}\cdot\mathbf{w}}{\Sigma\mathbf{W}}
ight]$

Open Calculator 🗹

20) Pore Pressure Ratio given Unit Weight

 $\mathbf{f}_{u} = \left(\frac{F_{u}}{\gamma \cdot z}\right)$

Open Calculator

 $\boxed{0.979444 = \left(\frac{52.89 kN/m^2}{18 kN/m^3 \cdot 3.0 m}\right)}$

21) Pore Water Pressure given Pore Pressure Ratio

 $\mathbf{f}\mathbf{x}egin{bmatrix} \mathbf{F}_{\mathrm{u}} = (\mathbf{r}_{\mathrm{u}}\cdot\mathbf{\gamma}\cdot\mathbf{z}) \end{bmatrix}$

Open Calculator

= $48.6 \mathrm{kN/m^2} = (0.9 \cdot 18 \mathrm{kN/m^3} \cdot 3.0 \mathrm{m})$

22) Radius of Arc when Total Shear Force on Slice is Available

 $\mathbf{f}\mathbf{x} = rac{\Sigma \mathbf{W} \cdot \mathbf{x}}{\Sigma \mathbf{S}}$

Open Calculator

 $= \frac{59.8 \text{N} \cdot 2.99 \text{m}}{32 \text{N}}$

23) Resultant Vertical Shear Force on Section N

fx

Open Calculator

 $ext{X}_{ ext{n}} = \left(ext{F}_{ ext{n}} \cdot ext{cos}igg(rac{ heta \cdot \pi}{180}igg)
ight) + \left(ext{S} \cdot ext{sin}igg(rac{ heta \cdot \pi}{180}igg)
ight) - ext{W} + ext{X}_{(ext{n}+1)}$

$$2.110605 ext{N} = \left(12.09 ext{N} \cdot \cos\left(rac{45\degree \cdot \pi}{180}
ight)
ight) + \left(11.07 ext{N} \cdot \sin\left(rac{45\degree \cdot \pi}{180}
ight)
ight) - 20.0 ext{N} + 9.87 ext{N}$$







24) Resultant Vertical Shear Force on Section N+1

fx

Open Calculator

$$X_{(n+1)} = W + X_n - \left(F_n \cdot \cos\left(rac{ heta \cdot \pi}{180}
ight)
ight) + \left(S \cdot \sin\left(rac{ heta \cdot \pi}{180}
ight)
ight)$$

ex

$$\left[10.95288 \text{N} = 20.0 \text{N} + 2.89 \text{N} - \left(12.09 \text{N} \cdot \cos\left(\frac{45° \cdot \pi}{180}\right)\right) + \left(11.07 \text{N} \cdot \sin\left(\frac{45° \cdot \pi}{180}\right)\right)\right]$$

25) Shear Force in Bishop's Analysis

fx $S = \tau \cdot 1$

Open Calculator

 $10.4562N = 1.11Pa \cdot 9.42m$

26) Shear Force in Bishop's Analysis given Factor of Safety

 $ext{S} = rac{\left(ext{c'} \cdot ext{l}
ight) + \left(ext{P} - \left(ext{u} \cdot ext{l}
ight)
ight) \cdot ext{tan} \left(rac{\phi' \cdot \pi}{180}
ight)}{ ext{f}_{ ext{s}}}$

Open Calculator 🗗

27) Shear Strength given Normal Stress on Slice 🗗

 $au = \left(c' + (\sigma_{normal} - u) \cdot tan\left(rac{\phi' \cdot \pi}{180}
ight)
ight)$

Open Calculator

$$\boxed{\textbf{ax} \ 3.986945 \text{Pa} = \left(4 \text{Pa} + (15.71 \text{Pa} - 20 \text{Pa}) \cdot \tan \left(\frac{9.99\degree \cdot \pi}{180}\right)\right)}$$



Open Calculator

28) Shear Stress given Shear Force in Bishop's Analysis 🗗

 $\boxed{\text{fx}} \boxed{\tau = \frac{\mathrm{S}}{\mathrm{1}}}$

_

 $= 1.175159 Pa = \frac{11.07 N}{9.42 m}$

29) Total Normal Force Acting at Base of Slice

fx $P = \sigma_{normal} \cdot l$

Open Calculator


 $\texttt{ex} \ 147.9882 N = 15.71 Pa \cdot 9.42 m$

fx $P = (\sigma' + \Sigma U) \cdot l$

30) Total Normal Force Acting at Base of Slice given Effective Stress

 $\mathbf{ex} \ 113.04 \mathrm{N} = (10 \mathrm{Pa} + 2 \mathrm{N}) \cdot 9.42 \mathrm{m}^{-1}$

31) Total Normal Force Acting on Slice given Weight of Slice



Open Calculator

Open Calculator 🗗

32) Total Shear Force on Slice given Radius of Arc

 $\Sigma S = rac{\Sigma W \cdot x}{r}$

Open Calculator





33) Total Weight of Slice given Total Shear Force on Slice

 $\Sigma W = rac{\Sigma S \cdot r}{x}$

Open Calculator 🗗

34) Unit weight of Soil given Pore Pressure Ratio

 $\boxed{\mathbf{f}\mathbf{z}} \gamma = \left(\frac{F_u}{r_u \cdot z}\right)$

Open Calculator

 $ext{ex} \left[19.58889 ext{kN/m}^3 = \left(rac{52.89 ext{kN/m}^2}{0.9 \cdot 3.0 ext{m}}
ight)
ight]$

35) Weight of Slice given Total Normal Force Acting on Slice

fx

Open Calculator

$$W = \left(F_n \cdot \cos\left(\frac{\theta \cdot \pi}{180}\right)\right) + \left(S \cdot \sin\left(\frac{\theta \cdot \pi}{180}\right)\right) - X_n + X_{(n+1)}$$

ex

$$19.2206 \text{N} = \left(12.09 \text{N} \cdot \cos\left(\frac{45° \cdot \pi}{180}\right)\right) + \left(11.07 \text{N} \cdot \sin\left(\frac{45° \cdot \pi}{180}\right)\right) - 2.89 \text{N} + 9.87 \text{N}$$





Variables Used

- B Pore Pressure Coefficient Overall
- C Cohesion in Soil (Pascal)
- c' Effective Cohesion (Pascal)
- Fn Total Normal Force in Soil Mechanics (Newton)
- fs Factor of Safety
- Fu Upward Force in Seepage Analysis (Kilonewton per Square Meter)
- Length of Arc (Meter)
- m Stability Coefficient m in Soil Mechanics
- n Stability Coefficient n
- P Total Normal Force (Newton)
- r Radius of Soil Section (Meter)
- r_u Pore Pressure Ratio
- S Shear Force on Slice in Soil Mechanics (Newton)
- u Upward Force (Pascal)
- w Width of Soil Section (Meter)
- W Weight of Slice (Newton)
- X Horizontal Distance (Meter)
- X_(n+1) Vertical Shear Force at other Section (Newton)
- X_n Vertical Shear Force (Newton)
- **z** Height of Slice (Meter)
- Y Unit Weight of Soil (Kilonewton per Cubic Meter)
- Δu Change in Pore Pressure (Pascal)
- Δσ₁ Change in Normal Stress (Pascal)
- ζ _{soil} Shear Strength (Megapascal)
- **0** Angle of Base (Degree)
- σ_{nm} Normal Stress in Mega Pascal (Megapascal)
- σ_{normal} Normal Stress in Pascal (Pascal)
- σ Effective Normal Stress (Pascal)





- ΣS Total Shear Force in Soil Mechanics (Newton)
- **ΣU** Total Pore Pressure (Newton)
- ΣW Total Weight of Slice in Soil Mechanics (Newton)
- T Shear Strength of Soil in Pascal (Pascal)
- φ' Effective Angle of Internal Friction (Degree)
- τ Shear Stress of Soil in Pascal (Pascal)





Constants, Functions, Measurements used

- Constant: pi, 3.14159265358979323846264338327950288
 Archimedes' constant
- Function: atan, atan(Number)

 Inverse trigonometric tangent function
- Function: cos, cos(Angle)

 Trigonometric cosine function
- Function: sin, sin(Angle)

 Trigonometric sine function
- Function: tan, tan(Angle)

 Trigonometric tangent function
- Measurement: Length in Meter (m)
 Length Unit Conversion
- Measurement: Pressure in Pascal (Pa), Megapascal (MPa), Kilonewton per Square Meter (kN/m²)
 - Pressure Unit Conversion
- Measurement: Force in Newton (N)
 Force Unit Conversion
- Measurement: Angle in Degree (°)

 Angle Unit Conversion
- Measurement: Specific Weight in Kilonewton per Cubic Meter (kN/m³)

 Specific Weight Unit Conversion
- Measurement: Stress in Pascal (Pa)
 Stress Unit Conversion





Check other formula lists

- Bearing Capacity for Strip Footing for C-Φ
 Earth Moving Formulas
 Lateral Pressure for Cohes
- Bearing Capacity of Cohesive Soil Formulas
- Bearing Capacity of Non-cohesive Soil
 Formulas
- Bearing Capacity of Soils: Meyerhof's Analysis Formulas
- Foundation Stability Analysis Formulas
- Atterberg Limits Formulas
- Bearing Capacity of Soil: Terzaghi's Analysis Formulas
- Compaction of Soil Formulas

- Lateral Pressure for Cohesive and Non Cohesive Soil Formulas
- Minimum Depth of Foundation by Rankine's Analysis Formulas
- Pile Foundations Formulas
- Scraper Production Formulas
- Slope Stability Analysis using Bishops Method Formulas
- Vibration Control in Blasting Formulas
- Void Ratio of Soil Sample Formulas
- Water Content of Soil and Related Formulas

Feel free to SHARE this document with your friends!

PDF Available in

English Spanish French German Russian Italian Portuguese Polish Dutch

1/2/2024 | 4:53:03 PM UTC

Please leave your feedback here..



