calculatoratoz.com

unitsconverters.com

Stability Analysis of Infinite Slopes in Prism Formulas

Calculators! Examples! Conversions!

Bookmark **calculatoratoz.com**, **unitsconverters.com**

Widest Coverage of Calculators and Growing - **30,000+ Calculators!**
Calculate With a Different Unit for Each Variable - **In built Unit Conversion!**
Widest Collection of Measurements and Units - **250+ Measurements!**

Feel free to SHARE this document with your friends!

Please leave your feedback here...

List of 23 Stability Analysis of Infinite Slopes in Prism Formulas

Stability Analysis of Infinite Slopes in Prism

1) Angle of Inclination given Horizontal Length of Prism

Open Calculator

fx $$I = a\cos\left(\frac{L}{b}\right)$$

ex $$78.46304^\circ = a\cos\left(\frac{2\text{m}}{10\text{m}}\right)$$

2) Angle of Inclination given Vertical Stress on Surface of Prism

Open Calculator

fx $$I = a\cos\left(\frac{\sigma_{\text{vertical}}}{z\cdot\gamma}\right)$$

ex $$89.98939^\circ = a\cos\left(\frac{10\text{Pa}}{3\text{m}\cdot 18\text{kN/m}^3}\right)$$

3) Angle of Inclination given Volume per Unit Length of Prism

Open Calculator

fx $$I = a\cos\left(\frac{V_l}{z\cdot b}\right)$$

ex $$80.40593^\circ = a\cos\left(\frac{5\text{m}^2}{3\text{m}\cdot 10\text{m}}\right)$$

4) Angle of Inclination given Weight of Soil Prism

Open Calculator

fx $$I = a\cos\left(\frac{W}{\gamma\cdot z\cdot b}\right)$$

ex $$79.32807^\circ = a\cos\left(\frac{100\text{kg}}{18\text{kN/m}^3\cdot 3\text{m}\cdot 10\text{m}}\right)$$

5) Cohesion given Factor of Safety for Cohesive Soil

Open Calculator

fx

$$c = \left(f_s - \left(\frac{\tan\left(\frac{\varphi \cdot \pi}{180}\right)}{\tan\left(\frac{I \cdot \pi}{180}\right)}\right)\right) \cdot \left(\gamma \cdot z \cdot \cos\left(\frac{I \cdot \pi}{180}\right) \cdot \sin\left(\frac{I \cdot \pi}{180}\right)\right)$$

ex

$$2.926924\text{kPa} = \left(2.8 - \left(\frac{\tan\left(\frac{46^\circ \cdot \pi}{180}\right)}{\tan\left(\frac{80^\circ \cdot \pi}{180}\right)}\right)\right) \cdot \left(18\text{kN/m}^3 \cdot 3\text{m} \cdot \cos\left(\frac{80^\circ \cdot \pi}{180}\right) \cdot \sin\left(\frac{80^\circ \cdot \pi}{180}\right)\right)$$

6) Depth of Prism given Factor of Safety for Cohesive Soil

Open Calculator

fx

$$z = \frac{c_u}{\left(f_s - \left(\frac{\tan((\Phi_i))}{\tan((I))}\right)\right) \cdot \gamma \cdot \cos((I)) \cdot \sin((I))}$$

ex

$$2.336534\text{m} = \frac{10\text{Pa}}{\left(2.8 - \left(\frac{\tan((82.87^\circ))}{\tan((80^\circ))}\right)\right) \cdot 18\text{kN/m}^3 \cdot \cos((80^\circ)) \cdot \sin((80^\circ))}$$

7) Depth of Prism given Vertical Stress on Surface of Prism

Open Calculator

fx

$$z = \frac{\sigma_{vertical}}{\gamma \cdot \cos((I))}$$

ex

$$3.199317\text{m} = \frac{10\text{Pa}}{18\text{kN/m}^3 \cdot \cos((80^\circ))}$$

8) Depth of Prism given Volume per Unit Length of Prism

Open Calculator

fx

$$z = \frac{V_l}{b \cdot \cos((I))}$$

ex

$$2.879385\text{m} = \frac{5\text{m}^2}{10\text{m} \cdot \cos((80^\circ))}$$

9) Depth of Prism given Weight of Soil Prism

Open Calculator

fx $$z = \frac{W}{\gamma \cdot b \cdot \cos((I))}$$

ex $$3.199317\text{m} = \frac{100\text{kg}}{18\text{kN/m}^3 \cdot 10\text{m} \cdot \cos((80^\circ))}$$

10) Factor of Safety for Cohesive Soil given Cohesion

Open Calculator

fx $$f_s = \left(\frac{c_u}{\gamma \cdot z \cdot \cos((I)) \cdot \sin((I))}\right) + \left(\frac{\tan((\Phi_i))}{\tan((I))}\right)$$

ex $$1.410703 = \left(\frac{10\text{Pa}}{18\text{kN/m}^3 \cdot 3\text{m} \cdot \cos((80^\circ)) \cdot \sin((80^\circ))}\right) + \left(\frac{\tan((82.87^\circ))}{\tan((80^\circ))}\right)$$

11) Horizontal Length of Prism

Open Calculator

fx $$L = b \cdot \cos((I))$$

ex $$1.736482\text{m} = 10\text{m} \cdot \cos((80^\circ))$$

12) Inclined Length along Slope given Horizontal Length of Prism

Open Calculator

fx $$b = \frac{L}{\cos((I))}$$

ex $$11.51754\text{m} = \frac{2\text{m}}{\cos((80^\circ))}$$

13) Inclined Length along Slope given Vertical Stress on Surface of Prism

Open Calculator

fx $$b = \frac{W}{\sigma_z} \cdot 5$$

ex $$50\text{m} = \frac{100\text{kg}}{10\text{MPa}} \cdot 5$$

14) Inclined Length along Slope given Volume Per Unit Length of Prism

Open Calculator

fx $$b = \frac{V_l}{z \cdot \cos((I))}$$

ex $$9.597951\text{m} = \frac{5\text{m}^2}{3\text{m} \cdot \cos((80^\circ))}$$

15) Inclined Length along Slope given Weight of Soil Prism

Open Calculator

fx $$b = \frac{W}{\gamma \cdot z \cdot \cos((I))}$$

ex $$10.66439\text{m} = \frac{100\text{kg}}{18\text{kN/m}^3 \cdot 3\text{m} \cdot \cos((80^\circ))}$$

16) Unit Weight of Soil given Factor of Safety for Cohesive Soil

Open Calculator

fx $$\gamma = \frac{c}{\left(f_s - \left(\frac{\tan\left(\frac{\varphi \cdot \pi}{180}\right)}{\tan\left(\frac{I \cdot \pi}{180}\right)}\right)\right) \cdot z \cdot \cos\left(\frac{I \cdot \pi}{180}\right) \cdot \sin\left(\frac{I \cdot \pi}{180}\right)}$$

ex $$18.5109\text{kN/m}^3 = \frac{3.01\text{kPa}}{\left(2.8 - \left(\frac{\tan\left(\frac{46^\circ \cdot \pi}{180}\right)}{\tan\left(\frac{80^\circ \cdot \pi}{180}\right)}\right)\right) \cdot 3\text{m} \cdot \cos\left(\frac{80^\circ \cdot \pi}{180}\right) \cdot \sin\left(\frac{80^\circ \cdot \pi}{180}\right)}$$

17) Unit Weight of Soil given Vertical Stress on Surface of Prism

Open Calculator

fx $$\gamma = \frac{\sigma_{vertical}}{z \cdot \cos((I))}$$

ex $$19.1959\text{kN/m}^3 = \frac{10\text{Pa}}{3\text{m} \cdot \cos((80^\circ))}$$

18) Unit Weight of Soil given Weight of Soil Prism

Open Calculator

fx $$\gamma = \frac{W}{z \cdot b \cdot \cos((I))}$$

ex $$19.1959\text{kN/m}^3 = \frac{100\text{kg}}{3\text{m} \cdot 10\text{m} \cdot \cos((80^\circ))}$$

19) Vertical Stress on Surface of Prism

Open Calculator

fx $$\sigma_z = \frac{W}{b}$$

ex $$1\text{E}^\wedge\text{-5MPa} = \frac{100\text{kg}}{10\text{m}}$$

20) Vertical Stress on Surface of Prism given Unit Weight of Soil

Open Calculator

fx $$\sigma_z = (z \cdot \gamma \cdot \cos((I)))$$

ex $$9.377002\text{MPa} = (3\text{m} \cdot 18\text{kN/m}^3 \cdot \cos((80^\circ)))$$

21) Volume Per Unit Length of Prism

Open Calculator

fx $$V_l = (z \cdot b \cdot \cos((I)))$$

ex $$5.209445\text{m}^2 = (3\text{m} \cdot 10\text{m} \cdot \cos((80^\circ)))$$

22) Weight of Soil Prism given Vertical Stress on Surface of Prism

Open Calculator

fx $$W = \sigma_{\text{vertical}} \cdot b$$

ex $$100\text{kg} = 10\text{Pa} \cdot 10\text{m}$$

23) Weight of Soil Prism in Stability Analysis

Open Calculator

fx $$W = (\gamma \cdot z \cdot b \cdot \cos((I)))$$

ex $$93.77002\text{kg} = (18\text{kN/m}^3 \cdot 3\text{m} \cdot 10\text{m} \cdot \cos((80^\circ)))$$

© calculatoratoz.com. A softusvista inc. venture!

Variables Used

- **b** Inclined Length *(Meter)*
- **c** Cohesion of Soil *(Kilopascal)*
- c_u Unit Cohesion *(Pascal)*
- f_s Factor of Safety
- **I** Angle of Inclination *(Degree)*
- **L** Horizontal Length of Prism *(Meter)*
- V_l Volume per unit length of prism *(Square Meter)*
- **W** Weight of Prism *(Kilogram)*
- **z** Depth of Prism *(Meter)*
- **γ** Unit Weight of Soil *(Kilonewton per Cubic Meter)*
- $\sigma_{vertical}$ Vertical Stress at a Point in Pascal *(Pascal)*
- σ_z Vertical Stress at a Point *(Megapascal)*
- **φ** Angle of Internal Friction *(Degree)*
- Φ_i Angle of Internal Friction of Soil *(Degree)*

© calculatoratoz.com. A softusvista inc. venture!

Constants, Functions, Measurements used

- Constant: **pi**, 3.14159265358979323846264338327950288
  Archimedes' constant
- Function: **acos**, acos(Number)
  Inverse trigonometric cosine function
- Function: **cos**, cos(Angle)
  Trigonometric cosine function
- Function: **sin**, sin(Angle)
  Trigonometric sine function
- Function: **tan**, tan(Angle)
  Trigonometric tangent function
- Measurement: **Length** in Meter (m)
  Length Unit Conversion
- Measurement: **Weight** in Kilogram (kg)
  Weight Unit Conversion
- Measurement: **Area** in Square Meter (m^2)
  Area Unit Conversion
- Measurement: **Pressure** in Pascal (Pa), Kilopascal (kPa), Megapascal (MPa)
  Pressure Unit Conversion
- Measurement: **Angle** in Degree (°)
  Angle Unit Conversion
- Measurement: **Specific Weight** in Kilonewton per Cubic Meter (kN/m^3)
  Specific Weight Unit Conversion

Check other formula lists

- Bearing Capacity for Strip Footing for C-Φ Soils Formulas
- Bearing Capacity of Cohesive Soil Formulas
- Bearing Capacity of Non-cohesive Soil Formulas
- Bearing Capacity of Soils: Meyerhof's Analysis Formulas
- Foundation Stability Analysis Formulas
- Atterberg Limits Formulas
- Bearing Capacity of Soil: Terzaghi's Analysis Formulas
- Compaction of Soil Formulas
- Earth Moving Formulas
- Lateral Pressure for Cohesive and Non Cohesive Soil Formulas
- Minimum Depth of Foundation by Rankine's Analysis Formulas
- Pile Foundations Formulas
- Scraper Production Formulas
- Seepage Analysis Formulas
- Slope Stability Analysis using Bishops Method Formulas
- Slope Stability Analysis using Culman's Method Formulas
- Soil Origin and Its Properties Formulas
- Specific Gravity of Soil Formulas
- Stability Analysis of Infinite Slopes in Prism Formulas
- Vibration Control in Blasting Formulas
- Void Ratio of Soil Sample Formulas
- Water Content of Soil and Related Formulas

Feel free to SHARE this document with your friends!

PDF Available in

English Spanish French German Russian Italian Portuguese Polish Dutch

1/16/2024 | 3:16:59 AM UTC

Please leave your feedback here...

© calculatoratoz.com. A softusvista inc. venture!