calculatoratoz.com

unitsconverters.com

Mechanics of Orthogonal Cutting Formulas

Calculators! Examples! Conversions!

Bookmark **calculatoratoz.com**, **unitsconverters.com**

Widest Coverage of Calculators and Growing - **30,000+ Calculators!**
Calculate With a Different Unit for Each Variable - **In built Unit Conversion!**
Widest Collection of Measurements and Units - **250+ Measurements!**

Feel free to SHARE this document with your friends!

Please leave your feedback here...

List of 10 Mechanics of Orthogonal Cutting Formulas

Mechanics of Orthogonal Cutting

1) Area of Cut from Tool Temperature

Open Calculator

fx $$A = \left(\frac{\theta \cdot k^{0.44} \cdot c^{0.56}}{C_0 \cdot U_s \cdot V^{0.44}} \right)^{\frac{100}{22}}$$

ex $$0.007347\text{m}^2 = \left(\frac{273^\circ\text{C} \cdot (10.18\text{W}/(\text{m*K}))^{0.44} \cdot (4.184\text{kJ}/\text{kg*K})^{0.56}}{0.29 \cdot 200\text{kJ}/\text{kg} \cdot (120\text{m}/\text{s})^{0.44}} \right)^{\frac{100}{22}}$$

2) Cutting Speed from Tool Temperature

Open Calculator

fx $$V = \left(\frac{\theta \cdot k^{0.44} \cdot c^{0.56}}{C_0 \cdot U_s \cdot A^{0.22}} \right)^{\frac{100}{44}}$$

ex $$2\text{m}/\text{s} = \left(\frac{273^\circ\text{C} \cdot (10.18\text{W}/(\text{m*K}))^{0.44} \cdot (4.184\text{kJ}/\text{kg*K})^{0.56}}{0.29 \cdot 200\text{kJ}/\text{kg} \cdot (26.4493\text{m}^2)^{0.22}} \right)^{\frac{100}{44}}$$

3) Cutting Speed given Spindle Speed

Open Calculator

fx $$V = \pi \cdot D \cdot N$$

ex $$2.001556\text{m}/\text{s} = \pi \cdot 0.01014\text{m} \cdot 600\text{rev}/\text{min}$$

4) Machining Time given Cutting Speed

Open Calculator

$$t = \frac{\pi \cdot D \cdot L}{f \cdot V}$$

$$1.137705\text{s} = \frac{\pi \cdot 0.01014\text{m} \cdot 3\text{m}}{0.70\text{mm/rev} \cdot 120\text{m/s}}$$

5) Machining Time given Spindle Speed

Open Calculator

$$t = \frac{L}{f \cdot N}$$

$$68.20926\text{s} = \frac{3\text{m}}{0.70\text{mm/rev} \cdot 600\text{rev/min}}$$

6) Nose Radius of Tool from Surface Finish Constraint

Open Calculator

$$r_{nose} = \frac{0.0321}{C}$$

$$0.107\text{m} = \frac{0.0321}{0.3\text{m}^{-1}}$$

7) Specific Cutting Energy Per Unit Cutting Force from Tool Temperature

Open Calculator

$$U_s = \frac{\theta \cdot c^{0.56} \cdot k^{0.44}}{C_0 \cdot V^{0.44} \cdot A^{0.22}}$$

$$33.00984\text{kJ/kg} = \frac{273^\circ\text{C} \cdot (4.184\text{kJ/kg*K})^{0.56} \cdot (10.18\text{W/(m*K)})^{0.44}}{0.29 \cdot (120\text{m/s})^{0.44} \cdot (26.4493\text{m}^2)^{0.22}}$$

8) Specific Heat of Work from Tool Temperature

Open Calculator

fx $$c = \left(\frac{C_0 \cdot U_s \cdot V^{0.44} \cdot A^{0.22}}{\theta \cdot k^{0.44}} \right)^{\frac{100}{56}}$$

ex $$104.4024\text{kJ/kg*K} = \left(\frac{0.29 \cdot 200\text{kJ/kg} \cdot (120\text{m/s})^{0.44} \cdot (26.4493\text{m}^2)^{0.22}}{273^\circ\text{C} \cdot (10.18\text{W/(m*K)})^{0.44}} \right)^{\frac{100}{56}}$$

9) Surface Finish Constraint

Open Calculator

fx $$C = \frac{0.0321}{r_{nose}}$$

ex $$0.3\text{m}^{-1} = \frac{0.0321}{0.107\text{m}}$$

10) Thermal Conductivity of Work from Tool Temperature

Open Calculator

fx $$k = \left(\frac{C_0 \cdot U_s \cdot V^{0.44} \cdot A^{0.22}}{\theta \cdot c^{0.56}} \right)^{\frac{100}{44}}$$

ex $$610.8\text{W/(m*K)} = \left(\frac{0.29 \cdot 200\text{kJ/kg} \cdot (120\text{m/s})^{0.44} \cdot (26.4493\text{m}^2)^{0.22}}{273^\circ\text{C} \cdot (4.184\text{kJ/kg*K})^{0.56}} \right)^{\frac{100}{44}}$$

Variables Used

- **A** Cutting Area *(Square Meter)*
- **c** Specific Heat Capacity *(Kilojoule per Kilogram per K)*
- **C** Feed Constraint *(1 per Meter)*
- C_0 Tool Temperature Constant
- **D** Workpiece Diameter *(Meter)*
- **f** Feed Rate *(Millimeter Per Revolution)*
- **k** Thermal Conductivity *(Watt per Meter per K)*
- **L** Length of Bar *(Meter)*
- **N** Spindle Speed *(Revolution per Minute)*
- r_{nose} Nose Radius *(Meter)*
- **t** Machining Time *(Second)*
- U_s Specific Cutting Energy *(Kilojoule per Kilogram)*
- **V** Cutting Velocity *(Meter per Second)*
- **θ** Tool Temperature *(Celsius)*

Constants, Functions, Measurements used

- Constant: **pi**, 3.14159265358979323846264338327950288
  Archimedes' constant
- Measurement: **Length** in Meter (m)
  Length Unit Conversion
- Measurement: **Time** in Second (s)
  Time Unit Conversion
- Measurement: **Temperature** in Celsius (°C)
  Temperature Unit Conversion
- Measurement: **Area** in Square Meter (m^2)
  Area Unit Conversion
- Measurement: **Speed** in Meter per Second (m/s)
  Speed Unit Conversion
- Measurement: **Thermal Conductivity** in Watt per Meter per K (W/(m*K))
  Thermal Conductivity Unit Conversion
- Measurement: **Specific Heat Capacity** in Kilojoule per Kilogram per K (kJ/kg*K)
  Specific Heat Capacity Unit Conversion
- Measurement: **Angular Velocity** in Revolution per Minute (rev/min)
  Angular Velocity Unit Conversion
- Measurement: **Specific Energy** in Kilojoule per Kilogram (kJ/kg)
  Specific Energy Unit Conversion
- Measurement: **Feed** in Millimeter Per Revolution (mm/rev)
  Feed Unit Conversion
- Measurement: **Reciprocal Length** in 1 per Meter (m^{-1})
  Reciprocal Length Unit Conversion

Check other formula lists

- **Mechanics of Orthogonal Cutting Formulas**

Feel free to SHARE this document with your friends!

PDF Available in

English Spanish French German Russian Italian Portuguese Polish Dutch

6/11/2024 | 9:39:00 AM UTC

Please leave your feedback here...