



calculatoratoz.com



unitsconverters.com

Forces and Loads on Joint Formulas

Calculators!

Examples!

Conversions!

Bookmark calculatoratoz.com, unitsconverters.com

Widest Coverage of Calculators and Growing - **30,000+ Calculators!**
Calculate With a Different Unit for Each Variable - **In built Unit Conversion!**
Widest Collection of Measurements and Units - **250+ Measurements!**

Feel free to SHARE this document with your friends!

[Please leave your feedback here...](#)



List of 8 Forces and Loads on Joint Formulas

Forces and Loads on Joint

1) Force on Cotter given Shear Stress in Cotter

$$fx \quad L = 2 \cdot t_c \cdot b \cdot \tau_{co}$$

[Open Calculator !\[\]\(a870788d6ed9b8fd294b7654a8c8526b_img.jpg\)](#)

$$ex \quad 32592N = 2 \cdot 14mm \cdot 48.5mm \cdot 24N/mm^2$$

2) Load Taken by Cotter Joint Rod given Tensile Stress in Rod

$$fx \quad L = \frac{\pi \cdot d^2 \cdot \sigma_{t_{rod}}}{4}$$

[Open Calculator !\[\]\(c50c8b7b2cc2cf9ff925edec0ee94c0d_img.jpg\)](#)

$$ex \quad 37738.38N = \frac{\pi \cdot (31mm)^2 \cdot 50N/mm^2}{4}$$

3) Load Taken by Socket of Cotter Joint given Compressive Stress

$$fx \quad L = \sigma_{cso} \cdot (d_4 - d_2) \cdot t_c$$

[Open Calculator !\[\]\(f60b7a900783ac3fd531bfd9c111be6d_img.jpg\)](#)

$$ex \quad 70000N = 125N/mm^2 \cdot (80mm - 40mm) \cdot 14mm$$

4) Load Taken by Socket of Cotter Joint given Shear Stress in Socket

$$fx \quad L = 2 \cdot (d_4 - d_2) \cdot c \cdot \tau_{so}$$

[Open Calculator !\[\]\(83bbbd261710c59db0214aa27b2edc0d_img.jpg\)](#)

$$ex \quad 44000N = 2 \cdot (80mm - 40mm) \cdot 22mm \cdot 25N/mm^2$$

5) Load Taken by Socket of Cotter Joint given Tensile Stress in Socket

$$fx \quad L = (\sigma_{tso}) \cdot \left(\frac{\pi}{4} \cdot (d_1^2 - d_2^2) - t_c \cdot (d_1 - d_2) \right)$$

[Open Calculator !\[\]\(f507db636256ac11a5525ef93ec6b8d7_img.jpg\)](#)

$$ex \quad 35848.59N = 42.8N/mm^2 \cdot \left(\frac{\pi}{4} \cdot ((54mm)^2 - (40mm)^2) - 14mm \cdot (54mm - 40mm) \right)$$



6) Load Taken by Spigot of Cotter Joint given Compressive Stress in Spigot Considering Crushing Failure

$$\text{fx } L = t_c \cdot d_2 \cdot \sigma_{c1}$$

[Open Calculator !\[\]\(cbe80b694ebd74fcfe136a095b608235_img.jpg\)](#)

$$\text{ex } 69440\text{N} = 14\text{mm} \cdot 40\text{mm} \cdot 124\text{N/mm}^2$$

7) Load Taken by Spigot of Cotter Joint given Shear Stress in Spigot

$$\text{fx } L = 2 \cdot a \cdot d_2 \cdot \tau_{sp}$$

[Open Calculator !\[\]\(3e2231b1ad3ca8da8658228c00dd08e0_img.jpg\)](#)

$$\text{ex } 48880\text{N} = 2 \cdot 23.5\text{mm} \cdot 40\text{mm} \cdot 26\text{N/mm}^2$$

8) Maximum Load taken by Cotter Joint given Spigot Diameter, Thickness and Stress

$$\text{fx } L = \left(\frac{\pi}{4} \cdot d_2^2 - d_2 \cdot t_c \right) \cdot (\sigma_{tsp})$$

[Open Calculator !\[\]\(0d5ec72f61334709c3fc9450209b754f_img.jpg\)](#)

$$\text{ex } 31696.99\text{N} = \left(\frac{\pi}{4} \cdot (40\text{mm})^2 - 40\text{mm} \cdot 14\text{mm} \right) \cdot 45.5\text{N/mm}^2$$






Variables Used

- **a** Gap between End of Slot to End of Spigot (Millimeter)
- **b** Mean Width of Cotter (Millimeter)
- **c** Axial Distance From Slot to End of Socket Collar (Millimeter)
- **d** Diameter of Rod of Cotter Joint (Millimeter)
- **d₁** Outside Diameter of Socket (Millimeter)
- **d₂** Diameter of Spigot (Millimeter)
- **d₄** Diameter of Socket Collar (Millimeter)
- **L** Load on Cotter Joint (Newton)
- **t_c** Thickness of Cotter (Millimeter)
- **σ_{c1}** Compressive Stress in Spigot (Newton per Square Millimeter)
- **σ_{cso}** Compressive Stress In Socket (Newton per Square Millimeter)
- **σ_{tso}** Tensile Stress In Socket (Newton per Square Millimeter)
- **σ_{tsp}** Tensile Stress In Spigot (Newton per Square Millimeter)
- **σ_{trod}** Tensile Stress in Cotter Joint Rod (Newton per Square Millimeter)
- **τ_{co}** Shear Stress in Cotter (Newton per Square Millimeter)
- **τ_{so}** Shear Stress in Socket (Newton per Square Millimeter)
- **τ_{sp}** Shear Stress in Spigot (Newton per Square Millimeter)



Constants, Functions, Measurements used

- **Constant:** **pi**, 3.14159265358979323846264338327950288
Archimedes' constant
- **Measurement:** **Length** in Millimeter (mm)
Length Unit Conversion 
- **Measurement:** **Force** in Newton (N)
Force Unit Conversion 
- **Measurement:** **Stress** in Newton per Square Millimeter (N/mm²)
Stress Unit Conversion 



Check other formula lists

- Forces and Loads on Joint Formulas 
- Strength and Stress Formulas 
- Joint Geometry and Dimensions Formulas 

Feel free to SHARE this document with your friends!

PDF Available in

[English](#) [Spanish](#) [French](#) [German](#) [Russian](#) [Italian](#) [Portuguese](#) [Polish](#) [Dutch](#)

1/8/2024 | 9:36:25 AM UTC

[Please leave your feedback here...](#)

