calculatoratoz.com

unitsconverters.com

Front Lateral Load Transfer for Race Cars Formulas

Calculators! Examples! Conversions!

Bookmark **calculatoratoz.com**, **unitsconverters.com**

Widest Coverage of Calculators and Growing - **30,000+ Calculators!**
Calculate With a Different Unit for Each Variable - **In built Unit Conversion!**
Widest Collection of Measurements and Units - **250+ Measurements!**

Feel free to SHARE this document with your friends!

Please leave your feedback here...

List of 9 Front Lateral Load Transfer for Race Cars Formulas

Front Lateral Load Transfer for Race Cars

1) COG Position Distance from Rear Wheels given Front Lateral Load Transfer

Open Calculator

fx $$x = \frac{W_f - \frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f}+K_{\Phi r}}}{\frac{Z_{rf}}{b}}$$

ex $$2.26802\text{m} = \frac{226\text{kg} - \frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad}+67800\text{Nm/rad}}}{\frac{245\text{m}}{2.7\text{m}}}$$

2) Front Lateral Load Transfer

Open Calculator

fx $$W_f = \frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}} + \frac{x}{b} \cdot Z_{rf}$$

ex $$228.9019\text{kg} = \frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}} + \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}$$

3) Front Roll Centre Height given Front Lateral Load Transfer

Open Calculator

fx $$Z_{rf} = \left(W_f - \frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}}\right) \cdot \frac{b}{x}$$

ex $$241.5934\text{m} = \left(226\text{kg} - \frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}}\right) \cdot \frac{2.7\text{m}}{2.3\text{m}}$$

4) Front Roll Rate given Front Lateral Load Transfer

Open Calculator

$$K_{\Phi f} = \frac{K_{\Phi r}}{\left(\frac{\frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot H}{\left(W_f - \frac{x}{b} \cdot Z_{rf}\right)}\right) - 1}$$

$$67659.57\text{Nm/rad} = \frac{67800\text{Nm/rad}}{\left(\frac{\frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m}}{\left(226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}\right)}\right) - 1}$$

5) Front Track Width given Front Lateral Load Transfer

Open Calculator

$$t_F = \frac{\frac{A_y}{[g]} \cdot m \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}}}{W_f - \frac{x}{b} \cdot Z_{rf}}$$

$$1.751662\text{m} = \frac{\frac{9.81\text{m/s}^2}{[g]} \cdot 155\text{kg} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}}}{226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}}$$

6) Height of Centre of Gravity from Roll Axis given Front Lateral Load Transfer

Open Calculator

$$H = \frac{W_f - \frac{x}{b} \cdot Z_{rf}}{\frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}}}$$

$$0.28687\text{m} = \frac{226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}}{\frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}}}$$

7) Lateral Acceleration given Front Lateral Load Transfer

Open Calculator

$$A_y = \frac{W_f - \frac{x}{b} \cdot Z_{rf}}{\frac{1}{[g]} \cdot \frac{m}{t_F} \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}}}$$

$$8.400592\text{m/s}^2 = \frac{226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}}{\frac{1}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}}}$$

8) Rear Roll Rate given Front Lateral Load Transfer

Open Calculator

$$K_{\Phi r} = K_{\Phi f} \cdot \left(\frac{\frac{A_y}{[g]} \cdot \frac{m}{t_F} \cdot H}{W_f - \frac{x}{b} \cdot Z_{rf}} - 1 \right)$$

$$95096.97\text{Nm/rad} = 94900\text{Nm/rad} \cdot \left(\frac{\frac{9.81\text{m/s}^2}{[g]} \cdot \frac{155\text{kg}}{1.5\text{m}} \cdot 0.335\text{m}}{226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}} - 1 \right)$$

9) Total Vehicle Mass given Front Lateral Load Transfer

Open Calculator

$$m = \frac{W_f - \frac{x}{b} \cdot Z_{rf}}{\frac{A_y}{[g]} \cdot \frac{1}{t_F} \cdot H \cdot \frac{K_{\Phi f}}{K_{\Phi f} + K_{\Phi r}}}$$

$$132.7311\text{kg} = \frac{226\text{kg} - \frac{2.3\text{m}}{2.7\text{m}} \cdot 245\text{m}}{\frac{9.81\text{m/s}^2}{[g]} \cdot \frac{1}{1.5\text{m}} \cdot 0.335\text{m} \cdot \frac{94900\text{Nm/rad}}{94900\text{Nm/rad} + 67800\text{Nm/rad}}}$$

Variables Used

- A_y Lateral Acceleration *(Meter per Square Second)*
- **b** Wheelbase of Vehicle *(Meter)*
- **H** Centre of Gravity Distance to Roll Axis *(Meter)*
- $K_{\Phi f}$ Front Roll Rate *(Newton Meter per Radian)*
- $K_{\Phi r}$ Rear Roll Rate *(Newton Meter per Radian)*
- **m** Mass of Vehicle *(Kilogram)*
- t_F Front Track Width *(Meter)*
- W_f Front Lateral Load Transfer *(Kilogram)*
- **x** Horizontal Distance of C.G. from Rear Axle *(Meter)*
- Z_{rf} Front Roll Centre Height *(Meter)*

Constants, Functions, Measurements used

- Constant: **[g]**, 9.80665
  Gravitational acceleration on Earth
- Measurement: **Length** in Meter (m)
  Length Unit Conversion
- Measurement: **Weight** in Kilogram (kg)
  Weight Unit Conversion
- Measurement: **Acceleration** in Meter per Square Second (m/s²)
  Acceleration Unit Conversion
- Measurement: **Torsion Constant** in Newton Meter per Radian (Nm/rad)
  Torsion Constant Unit Conversion

Check other formula lists

- **Load on Wheels in Race Cars Formulas**
- **Front Lateral Load Transfer for Race Cars Formulas**

Feel free to SHARE this document with your friends!

PDF Available in

English Spanish French German Russian Italian Portuguese Polish Dutch

8/12/2024 | 6:04:23 AM UTC *Please leave your feedback here...*